

# Alaska TENT & TARP

## Prospector & Miner Framed Wall Tent Setup Instructions

1. Make sure you have a clear area to setup your tent.
2. Lay out all of the pieces of the frame and place the angles 3' apart making an outline of the frame. There should be three rows of angles with four angles (two end angles and two center angles) in each row.
3. Put together the ridge poles, which are marked in **blue**. There are **three ridge poles** – two eaves and one ridge
  - a. Attach three pieces together, forming one long pole.
  - b. Slide two center angles onto each ridge pole. The center angles should cover the junctions of the pole sections.
  - c. Attach end angles to either end of the ridgepole.



Center Angles



End Angles

4. Put together the rafter poles, which are marked in **red**. There are **eight rafter poles** – four for each side of the tent.
  - a. Attach two pieces together, forming one long pole.
  - b. Place one end of the rafter pole into the angle on the eave and the other end of the rafter pole into the angle on the ridge.



Ridge Junction



Eave Junction

5. Place the wall tent on top of the frame.
  - a. Pull out the wall tent cover and lay it along the side of the frame.
  - b. Grab the bottom portion of the tent and pull up and over the frame.
  - c. Position each angle of the tent so it matches the angles of the frame.
  - d. Flip up the side walls above the eaves of the tent for easy installation of the leg poles.



# Alaska TENT & TARP

6. Install the legs on the tent, which are marked in **black**. There are **eight leg poles**.
  - a. Layout the leg poles so four are laying on each side of the tent.
  - b. Lift the edge of the tent and frame. Place the leg poles on the eave angles on one side of the tent.
  - c. Pull down the tent wall to ground level and make sure the angles of the tent are still matched up with the angles of the frame.
  - d. Install the leg poles on the opposite side of the tent using steps 6b and 6c.



7. Walk around the perimeter of the tent and pull down the tent walls to the ground.
8. Step inside of the tent and place the black sod cloth material at the bottom of the tent under the leg poles.



9. Tie out the tent based on the conditions you may experience while the tent is erect.
  - a. Stake down the wall of the tent around the perimeter.
  - b. Tie out the eaves of the tent on each side.

Your tent is now ready to be enjoyed in the great outdoors! For proper care of your wall tent, make sure you get the tent wet before you use it. This will allow the thread in the tent to swell up and fill the sewing needle puncture holes. Let the tent dry completely before packing it away. If you are going to be in wet conditions, it is recommended that you use a rain fly over your tent, which is sold separately at Alaska Tent & Tarp.

## Alaska Tent & Tarp

[www.alaskatent.com](http://www.alaskatent.com)

[sales@alaskatent.com](mailto:sales@alaskatent.com)

Fairbanks: 907-456-6328

Anchorage: 907-562-2293